
15NM95SZ

POWER MOSFET

15A, 950V N-CHANNEL SUPER-JUNCTION MOSFET




■ DESCRIPTION

The UTC **15NM95SZ** is a Super Junction MOSFET Structure and is designed to have better characteristics, such as fast switching time, low gate charge, low on-state resistance and a high rugged avalanche characteristics. This power MOSFET is usually used at AC-DC converters for power applications.

■ FEATURES

* $R_{DS(ON)} \leq 0.55\ \Omega$ @ V_{GS} = 10V, I_D = 7.5A
* Fast switching capability
* Avalanche energy tested
* Improved dv/dt capability, high ruggedness
* With ESD protection

■ SYMBOL



■ ORDERING INFORMATION


Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
15NM95SZL-TA3-T	15NM95SZG-TA3-T	TO-220	G	D	S	Tube
15NM95SZL-TF1-T	15NM95SZG-TF1-T	TO-220F1	G	D	S	Tube

Note: Pin Assignment: G: Gate D: Drain S: Source

15NM95SZG-TA3-T (1)Packing Type (2)Package Type (3)Green Package	(1) T: Tube (2) TA3: TO-220, TF1: TO-220F1 (3) G: Halogen Free and Lead Free, L: Lead Free

Copyright © 2026 Unisonic Technologies Co., Ltd

■ MARKING



■ ABSOLUTE MAXIMUM RATING (T_C = 25°C, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Drain-Source Voltage		V_{DSS}	950	V
Gate-Source Voltage		V_{GSS}	±20	V
Drain Current	DC	I_D	15	A
	Pulsed (Note 2)	I_{DM}	45	A
Avalanche Energy	Single Pulsed (Note 3)	E_{AS}	264	mJ
Peak Diode Recovery dv/dt (Note 4)		dv/dt	1.7	V/ns
Power Dissipation	TO-220	P_D	105	W
	TO-220F1		28	W
Junction Temperature		T_J	+150	°C
Storage Temperature Range		T_{STG}	-55 ~ +150	°C

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.
2. Repetitive Rating: Pulse width limited by maximum junction temperature.
3. L = 100mH, I_{AS} = 2.3A, V_{DD} = 50V, R_G = 25Ω, Starting T_J = 25°C.
4. I_{SD} ≤ 15A, di/dt ≤ 200A/μs, V_{DD} ≤ BV_{DSS}, Starting T_J = 25°C.

■ THERMAL DATA


PARAMETER		SYMBOL	RATINGS	UNIT
Junction to Ambient		θ_{JA}	62.5	°C/W
Junction to Case	TO-220	θ_{JC}	1.19	°C/W
	TO-220F1		4.46	°C/W

■ ELECTRICAL CHARACTERISTICS (T_J = 25°C, unless otherwise specified)


PARAMETER		SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS							
Drain-Source Breakdown Voltage		BV_{DSS}	V_{GS}=0V, I_D=250μA	950			V
Drain-Source Leakage Current		I_{DSS}	V_{DS}=950V, V_{GS}=0V			10	μA
Gate-Source Leakage Current	Forward	I_{GSS}	V_{GS}=+20V, V_{DS}=0V			+10	μA
	Reverse		V_{GS}=-20V, V_{DS}=0V			-10	μA
ON CHARACTERISTICS							
Gate Threshold Voltage		$V_{GS(TH)}$	V_{DS}=V_{GS}, I_D=250μA	3.0		4.5	V
Static Drain-Source On-State Resistance		$R_{DS(ON)}$	V_{GS}=10V, I_D=7.5A			0.55	Ω
DYNAMIC PARAMETERS							
Input Capacitance		C_{ISS}	V_{GS}=0V, V_{DS}=50V, f=1.0MHz		836		pF
Output Capacitance		C_{OSS}			104		pF
Reverse Transfer Capacitance		C_{RSS}			7		pF
SWITCHING PARAMETERS							
Total Gate Charge		Q_G	V_{DS}=760V, V_{GS}=10V, I_D=15A (Note 1, 2)		27		nC
Gate to Source Charge		Q_{GS}			9		nC
Gate to Drain Charge		Q_{GD}			3		nC
Turn-ON Delay Time		$t_{D(ON)}$	V_{DD}=100V, V_{GS}=10V, I_D=15A, R_G=25Ω (Note 1, 2)		14		ns
Rise Time		t_R			13		ns
Turn-OFF Delay Time		$t_{D(OFF)}$			56		ns
Fall-Time		t_F			25		ns
SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS							
Maximum Continuous Drain-Source Diode Forward Current		I_S				15	A
Maximum Pulsed Drain-Source Diode Forward Current		I_{SM}				45	A
Diode Forward Voltage		V_{SD}	I_F=15A, V_{GS}=0V			1.4	V
Reverse Recovery Time		t_{rr}	I_S=15A, V_{GS}=0V, dI_F/dt = 100 A/μs		414		ns
Reverse Recovery Charge (Note 1)		Q_{rr}			6.5		μC

Notes: 1. Pulse Test: Pulse width ≤ 300μs, Duty cycle ≤ 2%.
2. Essentially independent of operating temperature.

■ TEST CIRCUITS AND WAVEFORMS




Peak Diode Recovery dv/dt Test Circuit




Peak Diode Recovery dv/dt Waveforms


■ TEST CIRCUITS AND WAVEFORMS




Gate Charge Test Circuit




Gate Charge Waveforms




Resistive Switching Test Circuit



Resistive Switching Waveforms





Unclamped Inductive Switching Test Circuit





Unclamped Inductive Switching Waveforms


■ TYPICAL CHARACTERISTICS



















■ TYPICAL CHARACTERISTICS (Cont.)















■ TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.