



21NM60

Power MOSFET

21A, 600V N-CHANNEL SUPER-JUNCTION MOSFET



DESCRIPTION

The **UTC 21NM60** is a Super Junction MOSFET Structure and is designed to have better characteristics, such as fast switching time, low gate charge, low on-state resistance and a high rugged avalanche characteristics. This power MOSFET is usually used at AC-DC converters for power applications.

FEATURES

- * $R_{DS(ON)} \leq 0.19 \Omega$ @ $V_{GS}=10V$, $I_D=10.5A$
- * High Switching Speed
- * 100% Avalanche Tested


SYMBOL





■ ORDERING INFORMATION

Ordering Number		Package	Pin Assignment					Packing
Lead Free	Halogen Free		1	2	3	4	5	
21NM60L-TA3-T	21NM60G-TA3-T	TO-220	G	D	S	-	-	Tube
21NM60L-TF1-T	21NM60G-TF1-T	TO-220F1	G	D	S	-	-	Tube
21NM60L-TF2-T	21NM60G-TF2-T	TO-220F2	G	D	S	-	-	Tube
21NM60L-TF3-T	21NM60G-TF3-T	TO-220F	G	D	S	-	-	Tube
21NM60L-TW1-T	21NM60G-TW1-T	TO-220WF	G	D	S	-	-	Tube
21NM60L-TQ2-T	21NM60G-TQ2-T	TO-263	G	D	S	-	-	Tube
21NM60L-TQ2-R	21NM60G-TQ2-R	TO-263	G	D	S	-	-	Tape Reel
21NM60L-T3P-T	21NM60G-T3P-T	TO-3P	G	D	S	-	-	Tube
21NM60L-T3F-T	21NM60G-T3F-T	TO-3PF	G	D	S	-	-	Tube
21NM60L-T47-T	21NM60G-T47-T	TO-247	G	D	S	-	-	Tube
21NM60L-K04-8080-R	21NM60G-K04-8080-R	DFN8080-4	G	S	S	S	D	Tape Reel

Note: Pin Assignment: G: Gate D: Drain S: Source

21NM60G-TA3-T  (1) Packing Type (2) Package Type (3) Green Package	(1) T: Tube, R: Tape Reel (2) TA3: TO-220, TF3: TO-220F, TF1: TO-220F1, TF2: TO-220F2, T47: TO-247, TW1: TO-220WF, T3P: TO-3P, T3F: TO-3PF, TQ2: TO-263, K04-8080: DFN8080-4 (3) G: Halogen Free and Lead Free, L: Lead Free
---	---

■ MARKING

TO-220 / TO-220F / TO-220F1 / TO-220F2 TO-220WF / TO-263 / TO-3P / TO-3PF / TO-247	DFN8080-4
 UTC 21NM60 Lot Code → [] [] [] [] [] → L: Lead Free G: Halogen Free Date Code 1	 UTC 21NM60 Lot Code → • [] [] [] [] [] → Date Code

■ **ABSOLUTE MAXIMUM RATINGS** ($T_c=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Drain-Source Voltage		V_{DS}	600	V
Gate-Source Voltage		V_{GS}	± 30	V
Drain Current	Continuous	I_D	21	A
	Pulsed (Note 2)	I_{DM}	63	A
Avalanche Current (Note 3)		I_{AR}	4.4	A
Avalanche Energy		E_{AS}	706	mJ
Peak Diode Recovery dv/dt (Note 4)		dv/dt	20	V/ns
Power Dissipation	TO-220/TO-263	P_D	151	W
	TO-220F/TO-220F1		34	W
	TO-220F2/TO-220WF			
	TO-247		178	W
	TO-3P		208	W
	TO-3PF		69	W
	DFN8080-4		66	W
Junction Temperature		T_J	+150	$^{\circ}\text{C}$
Storage Temperature		T_{STG}	-55 ~ +150	$^{\circ}\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Repetitive Rating: Pulse width limited by maximum junction temperature.

3. $L = 73\text{mH}$, $I_{AS} = 4.4\text{A}$, $V_{DD} = 50\text{V}$, $R_G = 25\ \Omega$, Starting $T_J = 25^{\circ}\text{C}$

4. $I_{SD} \leq 21\text{A}$, $di/dt \leq 200\text{A}/\mu\text{s}$, $V_{DD} \leq BV_{DSS}$, Starting $T_J = 25^{\circ}\text{C}$

■ **THERMAL DATA**

PARAMETER		SYMBOL	RATINGS	UNIT
Junction to Ambient	TO-220/TO-220F TO-220F1/TO-220F2 TO-220WF/TO-263	θ_{JA}	62.5	$^{\circ}\text{C}/\text{W}$
	TO-247		60	$^{\circ}\text{C}/\text{W}$
	TO-3P/TO-3PF		40	$^{\circ}\text{C}/\text{W}$
	DFN8080-4		35	$^{\circ}\text{C}/\text{W}$
Junction to Case	TO-220/TO-263	θ_{JC}	0.83	$^{\circ}\text{C}/\text{W}$
	TO-220F/TO-220F1 TO-220F2/TO-220WF		3.7	$^{\circ}\text{C}/\text{W}$
	TO-247		0.7	$^{\circ}\text{C}/\text{W}$
	TO-3P		0.6	$^{\circ}\text{C}/\text{W}$
	TO-3PF		1.8	$^{\circ}\text{C}/\text{W}$
	DFN8080-4		1.89 (Note)	$^{\circ}\text{C}/\text{W}$

Note: Device mounted on FR-4 substrate P_c board, 2oz copper, with 1inch square copper plate.

■ **ELECTRICAL CHARACTERISTICS** ($T_J=25^\circ\text{C}$, unless otherwise specified)


PARAMETER		SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS							
Drain-Source Breakdown Voltage		BV _{DSS}	I _D =250μA, V _{GS} =0V	600			V
Drain-Source Leakage Current		I _{DSS}	V _{DS} =600V, V _{GS} =0V			10	μA
Gate- Source Leakage Current	Forward	I _{GSS}	V _{GS} =+30V, V _{DS} =0V			+100	nA
	Reverse		V _{GS} =-30V, V _{DS} =0V			-100	nA
ON CHARACTERISTICS							
Gate Threshold Voltage		V _{GS(TH)}	V _{DS} =V _{GS} , I _D =250μA	2.5		4.5	V
Static Drain-Source On-State Resistance		R _{DS(ON)}	V _{GS} =10V, I _D =10.5A			0.19	Ω
DYNAMIC PARAMETERS							
Input Capacitance		C _{ISS}	V _{GS} =0V, V _{DS} =50V, f=1.0MHz		1450		pF
Output Capacitance		C _{OSS}			250		pF
Reverse Transfer Capacitance		C _{RSS}			12		pF
SWITCHING PARAMETERS							
Total Gate Charge (Note 1)		Q _G	V _{DS} =480V, V _{GS} =10V, I _D =21A (Note1, 2)		74		nC
Gate to Source Charge		Q _{GS}			20		nC
Gate to Drain Charge		Q _{GD}			35		nC
Turn-ON Delay Time (Note 1)		t _{D(ON)}	V _{DS} =100V, V _{GS} =10V, I _D =21A, R _G =25Ω (Note1, 2)		28		ns
Rise Time		t _R			35		ns
Turn-OFF Delay Time		t _{D(OFF)}			170		ns
Fall-Time		t _F			60		ns
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS							
Maximum Body-Diode Continuous Current		I _S				21	A
Maximum Body-Diode Pulsed Current		I _{SM}				63	A
Drain-Source Diode Forward Voltage (Note 1)		V _{SD}	I _S =21A, V _{GS} =0V			1.4	V
Body Diode Reverse Recovery Time (Note 1)		t _{rr}	I _S =21A, V _{GS} =0V,		470		ns
Body Diode Reverse Recovery Charge		Q _{rr}	dl _F /dt=200A/μs		9.4		μC

Notes: 1. Pulse Test: Pulse width $\leq 300\mu\text{s}$, Duty cycle $\leq 2\%$.


2. Essentially independent of operating ambient temperature.

■ TEST CIRCUITS AND WAVEFORMS


Gate Charge Test Circuit




Gate Charge Waveforms




Resistive Switching Test Circuit




Resistive Switching Waveforms









Unclamped Inductive Switching Test Circuit









Unclamped Inductive Switching Waveforms






■ TYPICAL CHARACTERISTICS



TYPICAL CHARACTERISTICS (Cont.)



■ TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.