


**2N60A-LC1****Power MOSFET****2A, 600V N-CHANNEL
POWER MOSFET****DESCRIPTION**

The UTC **2N60A-LC1** is an N-channel power MOSFET using UTC's advanced technology to provide customers with a minimum on-state resistance and superior switching performance.

The UTC **2N60A-LC1** is generally applied in low power switching mode power appliances and electronic ballast.

FEATURES


- * $R_{DS(ON)} \leq 6.3 \Omega$ @ $V_{GS}=10V$, $I_D=1.0A$
- * High Switching Speed
- * 100% Avalanche Tested

SYMBOL**ORDERING INFORMATION**

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
2N60AL-TF1-T	2N60AG-TF1-T	TO-220F1	G	D	S	Tube
2N60AL-TF2-T	2N60AG-TF2-T	TO-220F2	G	D	S	Tube
2N60AL-TN3-R	2N60AG-TN3-R	TO-252	G	D	S	Tape Reel

Note: Pin Assignment: G: Gate D: Drain S: Source

2N60AG-TF1-T (1) Packing Type (2) Package Type (3) Green Package	(1) T: Tube (2) TF1: TO-220F1, TF2: TO-220F2, TM3: TO-251 (3) G: Halogen Free and Lead Free, L: Lead Free
--	--

MARKING

■ ABSOLUTE MAXIMUM RATINGS ($T_C=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Drain-Source Voltage		V_{DSS}	600	V
Gate-Source Voltage		V_{GSS}	± 30	V
Drain Current	Continuous	I_D	2	A
	Pulsed (Note 2)	I_{DM}	4	A
Avalanche Energy	Single Pulsed (Note 3)	E_{AS}	60	mJ
Peak Diode Recovery dv/dt (Note 4)		dv/dt	2.2	V/ns
Power Dissipation		P_D	35	W
Junction Temperature		T_J	+150	$^{\circ}\text{C}$
Storage Temperature		T_{STG}	-55 ~ +150	$^{\circ}\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Repetitive Rating: Pulse width limited by maximum junction temperature.

3. $L = 30\text{mH}$, $I_{AS} = 2\text{A}$, $V_{DD} = 50\text{V}$, $R_G = 25\Omega$, Starting $T_J = 25^{\circ}\text{C}$

4. $I_{SD} \leq 2.0\text{A}$, $di/dt \leq 200\text{A}/\mu\text{s}$, $V_{DD} \leq BV_{DSS}$, Starting $T_J = 25^{\circ}\text{C}$

■ THERMAL DATA

PARAMETER	SYMBOL	RATINGS	UNIT
Junction to Ambient	θ_{JA}	100	$^{\circ}\text{C}/\text{W}$
Junction to Case	θ_{JC}	3.57 (Note)	$^{\circ}\text{C}/\text{W}$

Note: Device mounted on FR-4 substrate PC board, 2oz copper, with 1inch square copper plate.


■ ELECTRICAL CHARACTERISTICS ($T_J=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS							
Drain-Source Breakdown Voltage		BV_{DSS}	$I_D=250\mu A, V_{GS}=0V$	600			V
Drain-Source Leakage Current		I_{DSS}	$V_{DS}=600V, V_{GS}=0V$			10	μA
Gate- Source Leakage Current	Forward	I_{GSS}	$V_{GS}=+30V, V_{DS}=0V$			+100	nA
	Reverse		$V_{GS}=-30V, V_{DS}=0V$			-100	nA
ON CHARACTERISTICS							
Gate Threshold Voltage		$V_{GS(TH)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	2.0		4.0	V
Static Drain-Source On-State Resistance		$R_{DS(ON)}$	$V_{GS}=10V, I_D=1.0A$			6.3	Ω
DYNAMIC PARAMETERS							
Input Capacitance		C_{ISS}	$V_{GS}=0V, V_{DS}=25V, f=1.0MHz$		246		pF
Output Capacitance		C_{OSS}			28		pF
Reverse Transfer Capacitance		C_{RSS}			2.4		pF
SWITCHING PARAMETERS							
Total Gate Charge (Note 1)		Q_G	$V_{DS}=480V, V_{GS}=10V, I_D=2A$ $I_G=1mA$ (Note 1, 2)		5		nC
Gate to Source Charge		Q_{GS}			2		nC
Gate to Drain Charge		Q_{GD}			1.3		nC
Turn-ON Delay Time (Note 1)		$t_{D(ON)}$	$V_{DD}=100V, V_{GS}=10V,$ $I_D=2A, R_G=25\Omega$ (Note 1, 2)		4		ns
Rise Time		t_R			16		ns
Turn-OFF Delay Time		$t_{D(OFF)}$			17		ns
Fall-Time		t_F			24		ns
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS							
Maximum Body-Diode Continuous Current		I_S				2	A
Maximum Body-Diode Pulsed Current (Note 1)		I_{SM}				4	A
Drain-Source Diode Forward Voltage (Note 1)		V_{SD}	$I_S=2A, V_{GS}=0V$			1.4	V
Body Diode Reverse Recovery Time		t_{rr}	$I_S=2A, V_{GS}=0V,$		280		ns
Body Diode Reverse Recovery Charge		Q_{rr}	$dI_F/dt=100A/\mu s$		0.9		μC


Notes: 1. Pulse Test: Pulse width $\leq 300\mu\text{s}$, Duty cycle $\leq 2\%$.

2. Essentially independent of operating temperature.


■ TEST CIRCUITS AND WAVEFORMS




Switching Test Circuit




Switching Waveforms




Gate Charge Test Circuit



Gate Charge Waveform









Unclamped Inductive Switching Test Circuit









Unclamped Inductive Switching Waveforms


TYPICAL CHARACTERISTICS



■ TYPICAL CHARACTERISTICS (Cont.)



TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.