


**2SC4617****NPN SILICON TRANSISTOR****GENERAL PURPOSE
TRANSISTOR****■ FEATURES**

* Low Cob

Cob=2.0pF (typ.)

* Complements the UTC 2SA1774

**■ ORDERING INFORMATION**

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
2SC4617L-x-AB3-R	2SC4617G-x-AB3-R	SOT-89	B	C	E	Tape Reel
2SC4617L-x-AE3-R	2SC4617G-x-AE3-R	SOT-23	B	E	C	Tape Reel
2SC4617L-x-AL3-R	2SC4617G-x-AL3-R	SOT-323	B	E	C	Tape Reel
2SC4617L-x-AN3-R	2SC4617G-x-AN3-R	SOT-523	B	E	C	Tape Reel
2SC4617L-x-AQ3-R	2SC4617G-x-AQ3-R	SOT-723	B	E	C	Tape Reel

Note: Pin assignment: B: Base C: Collector E: Emitter

2SC4617G-x-AB3-R (1) Packing Type (2) Package Type (3) Rank (4) Green Package	(1) R: Tape Reel (2) AB3: SOT-89, AE3: SOT-23, AL3: SOT-323, AN3: SOT-523, AQ3: SOT-723 (3) Refer to CLASSIFICATION OF h_{FE} (4) G: Halogen Free and Lead Free, L: Lead Free
---	---

■ MARKING

SOT-89	SOT-23 / SOT-323 / SOT-523 / SOT-723
Date Code C5 L: Lead Free G: Halogen Free	L: Lead Free G: Halogen Free

■ **ABSOLUTE MAXIMUM RATINGS** ($T_A=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Collector-Base Voltage		V_{CBO}	60	V
Collector-Emitter Voltage		V_{CEO}	50	V
Emitter-Base Voltage		V_{EBO}	7	V
Collector Current		I_C	0.15	A
Collector Power Dissipation	SOT-89	P_C	500	mW
	SOT-523		150	mW
	SOT-23/SOT-323		200	mW
	SOT-723		125	mW
Junction Temperature		T_J	+150	$^{\circ}\text{C}$
Storage Temperature		T_{STG}	-55 ~ +150	$^{\circ}\text{C}$

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.







■ **ELECTRICAL CHARACTERISTICS** ($T_A=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Collector Base Breakdown Voltage	BV_{CBO}	$I_C=50\mu\text{A}$	60			V
Collector Emitter Breakdown Voltage	BV_{CEO}	$I_C=1\text{mA}$	50			V
Emitter-base Breakdown Voltage	BV_{EBO}	$I_E=50\mu\text{A}$	7			V
Collector Cut-Off Current	I_{CBO}	$V_{CB}=60\text{V}$			0.1	μA
Emitter Cut-Off Current	I_{EBO}	$V_{EB}=7\text{V}$			0.1	μA
DC Current Gain	h_{FE}	$V_{CE}=6\text{V}$, $I_C=1\text{mA}$	120		560	
Collector-Emitter Saturation Voltage	$V_{CE(SAT)}$	$I_C=50\text{mA}$, $I_B=5\text{mA}$			0.4	V
Transition Frequency	f_T	$V_{CE}=12\text{V}$, $I_E=-2\text{mA}$, $f=100\text{MHz}$		180		MHz
Output Capacitance	C_{ob}	$V_{CE}=12\text{V}$, $I_E=0\text{A}$, $f=1\text{MHz}$		2	3.5	pF





■ **CLASSIFICATION OF h_{FE}**

RANK	Q	R	S
RANGE	120 ~ 270	180 ~ 390	270 ~ 560

■ TYPICAL CHARACTERISTICS



■ TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.