



5N100-FCQ

Power MOSFET

5.0A, 1000V N-CHANNEL POWER MOSFET



DESCRIPTION

The UTC **5N100-FCQ** provide excellent $R_{DS(ON)}$, low gate charge and operation with low gate voltages. This device is suitable for use as a load switch or in PWM applications.

FEATURES

- * $R_{DS(ON)} \leq 5.4 \Omega$ @ $V_{GS}=10V$, $I_D=1.0A$
- * Fast switching capability
- * Avalanche energy specified
- * Improved dv/dt capability, high ruggedness

SYMBOL




ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
5N100L-TA3-T	5N100G-TA3-T	TO-220	G	D	S	Tube
5N100L-TF1-T	5N100G-TF1-T	TO-220F1	G	D	S	Tube
5N100L-TF2-T	5N100G-TF2-T	TO-220F2	G	D	S	Tube
5N100L-TF3-T	5N100G-TF3-T	TO-220F	G	D	S	Tube
5N100L-TN3-R	5N100G-TN3-R	TO-252	G	D	S	Tape Reel

Note: Pin Assignment: G: Gate D: Drain S: Source

5N100G-TA3-T (1) Packing Type (2) Package Type (3) Green Package	(1) T: Tube, R: Tape Reel (2) TA3: TO-220, TF3: TO-220F, TF1: TO-220F1, TF2: TO-220F2, TN3: TO-252 (3) G: Halogen Free and Lead Free, L: Lead Free
--	---

■ MARKING



■ **ABSOLUTE MAXIMUM RATINGS** ($T_C=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Drain-Source Voltage		V_{DSS}	1000	V
Gate-Source Voltage		V_{GSS}	± 30	V
Continuous Drain Current		I_D	5	A
Pulsed Drain Current (Note 2)		I_{DM}	10	A
Avalanche Energy (Note 3)	Single Pulsed	E_{AS}	173	mJ
Peak Diode Recovery dv/dt (Note 4)		dv/dt	2.5	V/ns
Power Dissipation	TO-220	P_D	135	W
	TO-220F/TO-220F1		25	W
	TO-220F2		48	W
	TO-252			
Junction Temperature		T_J	+150	$^{\circ}\text{C}$
Storage Temperature		T_{STG}	-55 ~ +150	$^{\circ}\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Repetitive Rating: Pulse width limited by maximum junction temperature.

3. $L=30\text{mH}$, $I_{AS}=3.4\text{A}$, $V_{DD}=100\text{V}$, $R_G=25\ \Omega$, Starting $T_J = 25^{\circ}\text{C}$

4. $I_{SD} \leq 5.0\text{A}$, $di/dt \leq 200\text{A}/\mu\text{s}$, $V_{DD} \leq BV_{DSS}$, Starting $T_J = 25^{\circ}\text{C}$

■ **THERMAL DATA**

PARAMETER		SYMBOL	RATINGS	UNIT
Junction to Ambient	TO-220/TO-220F/ TO-220F1/TO-220F2	θ_{JA}	62.5	$^{\circ}\text{C}/\text{W}$
	TO-252	θ_{JA}	110	$^{\circ}\text{C}/\text{W}$
	TO-220	θ_{JC}	0.92	$^{\circ}\text{C}/\text{W}$
Junction to Case	TO-220F/TO-220F1		5	$^{\circ}\text{C}/\text{W}$
	TO-220F2			
	TO-252		2.6	$^{\circ}\text{C}/\text{W}$


■ **ELECTRICAL CHARACTERISTICS** ($T_J=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS							
Drain-Source Breakdown Voltage		BV_{DSS}	$V_{GS} = 0V, I_D = 250\mu A$	1000			V
Drain-Source Leakage Current		I_{DSS}	$V_{DS} = 1000V, V_{GS} = 0V$			10	μA
Gate-Source Leakage Current	Forward	I_{GSS}	$V_{GS} = 30V, V_{DS} = 0V$			100	nA
	Reverse		$V_{GS} = -30V, V_{DS} = 0V$			-100	nA
ON CHARACTERISTICS							
Gate Threshold Voltage		$V_{GS(TH)}$	$V_{DS} = V_{GS}, I_D = 250\mu A$	3.0		5.0	V
Static Drain-Source On-State Resistance		$R_{DS(ON)}$	$V_{GS} = 10V, I_D = 1.0A$			5.4	Ω
DYNAMIC CHARACTERISTICS							
Input Capacitance		C_{ISS}	$V_{DS} = 25V, V_{GS} = 0V, f = 1MHz$		726		pF
Output Capacitance		C_{OSS}			62		pF
Reverse Transfer Capacitance		C_{RSS}			1.8		pF
SWITCHING CHARACTERISTICS							
Total Gate Charge		Q_G	$V_{DS} = 800V, V_{GS} = 10V, I_D = 5A, I_G = 1mA$ (Note 1, 2)		12		nC
Gate-Source Charge		Q_{GS}			6		nC
Gate-Drain Charge		Q_{GD}			0.6		nC
Turn-On Delay Time		$t_{D(ON)}$	$V_{DD} = 100V, V_{GS} = 10V, I_D = 5A, R_G = 25\Omega$ (Note 1, 2)		12		ns
Turn-On Rise Time		t_R			16		ns
Turn-Off Delay Time		$t_{D(OFF)}$			24		ns
Turn-Off Fall Time		t_F			30		ns
DRAIN-SOURCE DIODE CHARACTERISTICS							
Maximum Body-Diode Continuous Current		I_S				5	A
Continuous Drain-Source Current		I_{SD}				10	A
Drain-Source Diode Forward Voltage		V_{SD}	$I_S = 5A, V_{GS} = 0V$			1.4	V
Reverse Recovery Time		t_{rr}	$I_F = 5A, di/dt = 100A/\mu s$		510		ns
Reverse Recovery Charge		Q_{rr}			9.1		μC


Notes: 1. Pulse Test: Pulse width $\leq 300\mu s$, Duty cycle $\leq 2\%$.

2. Essentially independent of operating temperature.

■ TEST CIRCUITS AND WAVEFORMS




Peak Diode Recovery dv/dt Test Circuit




Peak Diode Recovery dv/dt Waveforms


■ TEST CIRCUITS AND WAVEFORMS




Switching Test Circuit




Switching Waveforms




Gate Charge Test Circuit



Gate Charge Waveform









Unclamped Inductive Switching Test Circuit









Unclamped Inductive Switching Waveforms


TYPICAL CHARACTERISTICS



TYPICAL CHARACTERISTICS (Cont.)



■ TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.