



D44VH10

NPN SILICON TRANSISTOR


NPN COMPLEMENTARY SILICON POWER TRANSISTORS

DESCRIPTION

The UTC **D44VH10** is complementary silicon power transistors are designed for high-speed switching applications, such as switching regulators and high frequency inverters. The devices are also well-suited for drivers for high power switching circuits.

FEATURES

- * Low Collector-Emitter Saturation Voltage:
 $V_{CE(SAT)}=0.4V$ (Max.) @ 8.0A
- * Complementary Pairs Simplify Circuit Designs




ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
D44VH10L-TA3-T	D44VH10G-TA3-T	TO-220	B	C	E	Tube

Note: Pin Assignment: B: Base C: Collector E: Emitter

<p>D44VH10G-TA3-T</p> <p>(1) Packing Type</p> <p>(2) Package Type</p> <p>(3) Green Package</p>	<p>(1) R: Tape Reel</p> <p>(2) TA3: TO-220</p> <p>(3) G: Halogen Free and Lead Free, L: Lead Free</p>
--	---

MARKING



■ ABSOLUTE MAXIMUM RATING ($T_A=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Collector-Base Voltage		V_{CBO}	100	V
Collector-Emitter Voltage		V_{CEO}	80	V
Emitter-Base Voltage		V_{EBO}	7	V
Collector Current	DC	I_C	15	A
	Pulse(Note 2)	I_{CM}	20	A
Power Dissipation	$T_C=25^{\circ}\text{C}$	P_D	83	W
Junction Temperature		T_J	$-40 \sim +150$	$^{\circ}\text{C}$
Storage Temperature		T_{STG}	$-55 \sim +150$	$^{\circ}\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.







2. Pulse Width $\leq 6.0\text{ms}$, Duty Cycle $\leq 50\%$.

■ ELECTRICAL CHARACTERISTICS ($T_C=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS						
Collector-Emitter Sustaining Voltage	$V_{CEQ(SUS)}$	$I_C=25\text{mA}$, $I_B=0$	80			V
Collector-Emitter Cutoff Current	I_{CEV}	$V_{CE}=\text{Rated } V_{CEV}$, $V_{BE(OFF)}=-4.0\text{V}$			10	μA
Emitter Cutoff Current	I_{EBO}	$V_{EB}=7.0\text{V}$, $I_C=0$			10	μA
ON CHARACTERISTICS(Note)						
DC Current Gain	h_{FE}	$V_{CE}=1.0\text{V}$, $I_C=2.0\text{A}$	35			
		$V_{CE}=1.0\text{V}$, $I_C=4.0\text{A}$	20			
Collector-Emitter Saturation Voltage	$V_{CE(SAT)}$	$I_C=8.0\text{A}$, $I_B=0.4\text{A}$			0.4	V
Base-Emitter Saturation Voltage	$V_{BE(SAT)}$	$I_C=8.0\text{A}$, $I_B=0.4\text{A}$			1.5	V
DYNAMIC CHARACTERISTICS						
Current Gain Bandwidth Product	f_T			50		MHz
Output Capacitance	C_{ob}			120		pF

Note: Pulse test: Pulse Width $\leq 300\mu\text{s}$, Duty Cycle $\leq 2\%$.

TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.