

**SK86**



Preliminary

DIODE**8A, 60V SCHOTTKY RECTIFIER****DESCRIPTION**

The UTC **SK86** is a schottky rectifier diode, it uses UTC's advanced technology to provide customers with low forward voltage and high current capability, etc.

FEATURES

- * High current capability
- * Low forward voltage

SYMBOL**ORDERING INFORMATION**

Ordering Number		Package	Pin Assignment		Packing
Lead Free	Halogen Free		1	2	
SK86-SMC-R	SK86-SMC-R	SMC	K	A	Tape Reel

Note: Pin Assignment: A: Anode, K: Cathode

 SK86L-SMC-R (1) Packing Type (2) Package Type (3) Lead Free	 (1) R: Tape Reel (2) SMC: SMC (3) L: Lead Free, G: Halogen Free
--	---

■ ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	RATINGS	UNIT
RMS Voltage	V_{RMS}	42	V
Recurrent Peak Reverse Voltage	V_R	60	V
DC Blocking Voltage	V_B	60	V
Storage Temperature	T_{STG}	-55~+125	°C
Operating Temperature	T_{OPR}	-55~+125	°C
Junction Temperature	T_J	150	°C
Thermal Resistance Junction To Lead	θ_{JL}	18	°C/W

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.
Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ ELECTRICAL CHARACTERISTICS ($T_J=25^{\circ}\text{C}$ unless otherwise specified.)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Average Forward Current	$I_{F(AV)}$	$T_L=95^{\circ}\text{C}$		8.0		A
Peak Forward Surge Current	I_{FSM}	8.3ms, Half Sine		200		A
Instantaneous Forward Voltage	V_F	$I_{FM}=8.0\text{A}$, $T_J=25^{\circ}\text{C}$ (Note 1)			0.65	V
DC Reverse Current At	I_R	$T_J=25^{\circ}\text{C}$			1	mA
Rated DC Blocking Voltage		$T_J=100^{\circ}\text{C}$			20	mA
Junction Capacitance	C_J	Measured at 1.0MHz, $V_R=4.0\text{V}$		400		pF

Note: 1. High temperature solder exemptions applied.

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.