



TGBR5S100

Preliminary

DIODE

TRENCH MOS SCHOTTKY BARRIER RECTIFIER



DESCRIPTION


The UTC **TGBR5S100** is a trench mos schottky barrier rectifier, it uses UTC's advanced technology to provide customers with low forward voltage drop and high switching speed, etc.

FEATURES

- * Super low forward voltage drop
- * High switching speed

SYMBOL


DO-201AD	TO-220F1 / TO-277
	






ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
TGBR5S100L-TF1-T	TGBR5S100G-TF1-T	TO-220F1	A	K	A	Tube
TGBR5S100L-T27-T	TGBR5S100G-T27-T	TO-277	A	K	A	Tape Reel
TGBR5S100L-Z21D-B	TGBR5S100G-Z21D-B	DO-201AD	K	A	-	Tape Box
TGBR5S100L-Z21D-R	TGBR5S100G-Z21D-R	DO-201AD	K	A	-	Tape Reel
TGBR5S100L-Z21D-K	TGBR5S100G-Z21D-K	DO-201AD	K	A	-	Bulk

Note: Pin Assignment: A: Anode K: Cathode

	(1) Packing Type	(1) T: Tube, B: Tape Box, R: Tape Reel, K: Bulk (2) TF1: TO-220F1, T27: TO-277, Z21D: DO-201AD (3) G: Halogen Free and Lead Free, L: Lead Free
	(2) Package Type	
	(3) Green Package	

MARKING

PACKAGE	MARKING
TO-220F1	 <p>Lot Code → 1 → Date Code</p> <p>L: Lead Free G: Halogen Free</p>
TO-277	 <p>Lot Code → Date Code</p> <p>L: Lead Free G: Halogen Free</p>
DO-201AD	 <p>Cathode Band for uni-directional Only</p> <p>L: Lead Free G: Halogen Free Date Code</p>

■ ABSOLUTE MAXIMUM RATINGS (T_A=25°C, unless otherwise specified)

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitance load, derate current by 20%.

PARAMETER	SYMBOL	RATINGS	UNIT
DC Blocking Voltage	V _{RM}	100	V
Working Peak Reverse Voltage	V _{RWM}	100	V
Peak Repetitive Reverse Voltage	V _{RRM}	100	V
Average Rectified Output Current	I _O	5	A
Non-Repetitive Peak Forward Surge Current 8.3ms Single Half Sine-Wave Superimposed on Rated Load	I _{FSM}	150	A
Operating Junction Temperature	T _J	-65 ~ +150	°C
Storage Temperature	T _{STG}	-65 ~ +150	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL CHARACTERISTICS (PER LEG)

PARAMETER	SYMBOL	RATINGS	UNIT
Typical Thermal Resistance	TO-220F1	4	°C/W
	TO-277	4 (Note)	°C/W
	DO-201AD	22	°C/W

Note: FR-4 PCB, 2 oz Copper. Minimum recommended pad layout.

■ ELECTRICAL CHARACTERISTICS (PER LEG) (T_A=25°C, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Reverse Breakdown Voltage	V _{(BR)R}	I _R =0.5mA	100			V
Forward Voltage Drop	V _{FM}	I _F =1A, T _J =25°C		0.41		V
		I _F =1A, T _J =125°C		0.31		V
		I _F =3A, T _J =25°C		0.50		V
		I _F =3A, T _J =125°C		0.45		V
		I _F =5A, T _J =25°C		0.58	0.60	V
		I _F =5A, T _J =125°C		0.51	0.55	V
Leakage Current	I _{RM}	V _R =100V, T _J =25°C		15	300	μA
		V _R =100V, T _J =125°C		8	30	mA

Note: Pulse Test: Pulse width ≤ 300μs, Duty cycle ≤ 2%.

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.