

**U74LVC1G17****CMOS IC****SINGLE SCHMITT-TRIGGER
BUFFER****DESCRIPTION**

The UTC **U74LVC1G17** is a single Schmitt-trigger buffer, it provides the function $Y=A$.

The device have different input threshold levels for positive-going (V_{T+}) and negative-going (V_{T-}) signals because of the Schmitt-trigger action in the input.

This device has power-down protective circuit, preventing device destruction when it is powered down.



FEATURES

- * Operation Voltage Range: 1.65V ~ 5.5V
- * Low Power Current: $I_{CC}=10\mu A$ (Max.)
- * $\pm 24mA$ Output Drive ($V_{CC}=3.0V$)
- * Power Down Protection


ORDERING INFORMATION

Ordering Number		Package	Packing
Lead Free	Halogen Free		
U74LVC1G17L-AE5-R	U74LVC1G17G-AE5-R	SOT-23-5	Tape Reel
U74LVC1G17L-AF5-R	U74LVC1G17G-AF5-R	SOT-25	Tape Reel
U74LVC1G17L-AL5-R	U74LVC1G17G-AL5-R	SOT-353	Tape Reel

U74LVC1G17G-AF5-R	(1) Packing Type (2) Package Type (3) Green Package	(1) R: Tape Reel (2) AE5: SOT-23-5, AF5: SOT-25, AL5: SOT-353 (3) G: Halogen Free and Lead Free, L: Lead Free
-------------------	---	---

MARKING



■ PIN CONFIGURATION



■ FUNCTION TABLE (each gate)

INPUT	OUTPUT
A	Y
L	L
H	H

■ LOGIC DIAGRAM (positive logic)



■ ABSOLUTE MAXIMUM RATING (T_A=25°C, unless otherwise specified) (Note 2)

PARAMETER	SYMBOL	TEST CONDITIONS	RATINGS	UNIT
Supply Voltage	V _{CC}		-0.5 ~ 6.5	V
Input Voltage	V _{IN}		-0.5 ~ 6.5	V
Output Voltage	V _{OUT}	Output in the high or low state	-0.5 ~ V _{CC} +0.5	V
		Output in the power-off state	-0.5 ~ 6.5	V
Continuous V _{CC} or GND Current	I _{CC}		±100	mA
Continuous Output Current	I _{OUT}		±50	mA
Input Clamp Current	I _{IK}	V _{IN} <0	-50	mA
Output Clamp Current	I _{OK}	V _{OUT} <0	-50	mA
Junction Temperature	T _J		+150	°C
Storage Temperature Range	T _{STG}		-65 ~ +150	°C

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. The input and output voltage ratings may be exceeded if the input and output current ratings are observed.

■ THERMAL DATA

PARAMETER		SYMBOL	RATINGS	UNIT
Junction to Ambient	SOT-23-5	θ _{JA}	280	°C/W
	SOT-25		230	°C/W
	SOT-353		350	°C/W
Junction to Case	SOT-23-5	θ _{JC}	100	°C/W
	SOT-25		90	°C/W
	SOT-353		120	°C/W

■ RECOMMENDED OPERATING CONDITIONS

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Supply Voltage	V _{CC}	Operating	1.65		5.5	V
		Data retention only	1.5			V
Input Voltage	V _{IN}		0		5.5	V
Output Voltage	V _{OUT}	High or low state	0		V _{CC}	V
Operating Temperature	T _A		-40		+125	°C

■ STATIC CHARACTERISTICS

PARAMETER	SYMBOL	TEST CONDITIONS	T _A =25°C			T _A =-40~+125°C			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
Positive-going Input Threshold Voltage	V _{T+}	V _{CC} =1.65V	0.76		1.16	0.73		1.16	V
		V _{CC} =2.3V	1.08		1.56	1.05		1.56	V
		V _{CC} =3.0V	1.48		1.92	1.45		1.92	V
		V _{CC} =4.5V	2.16		2.74	2.13		2.74	V
		V _{CC} =5.5V	2.61		3.33	2.58		3.33	V
Negative-going Input Threshold Voltage	V _{T-}	V _{CC} =1.65V	0.35		0.62	0.35		0.65	V
		V _{CC} =2.3V	0.56		0.88	0.56		0.91	V
		V _{CC} =3.0V	0.84		1.2	0.84		1.23	V
		V _{CC} =4.5V	1.41		1.97	1.41		2.0	V
		V _{CC} =5.5V	1.87		2.4	1.87		2.43	V
Hysteresis Voltage (V _{T+} -V _{T-})	ΔV _T	V _{CC} =1.65V	0.36		0.64	0.3		0.64	V
		V _{CC} =2.3V	0.45		0.78	0.39		0.78	V
		V _{CC} =3.0V	0.51		0.87	0.45		0.87	V
		V _{CC} =4.5V	0.58		1.04	0.52		1.04	V
		V _{CC} =5.5V	0.69		1.11	0.63		1.11	V

■ STATIC CHARACTERISTICS (Cont.)

PARAMETER	SYMBOL	TEST CONDITIONS	T _A =25°C			T _A =-40~+125°C			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
High-Level Output Voltage	V _{OH}	V _{CC} =1.65V~5.5V, I _{OH} =-100μA	V _{CC} -0.1			V _{CC} -0.1			V
		V _{CC} = 1.65V, I _{OH} =-4mA	1.2			0.95			V
		V _{CC} = 2.3V, I _{OH} =-8mA	1.9			1.7			V
		V _{CC} = 3.0V	I _{OH} =-16mA	2.4		2.1			V
			I _{OH} =-24mA	2.3		2.0			V
		V _{CC} = 4.5V, I _{OH} =-32mA	3.8			3.4			V
Low-Level Output Voltage	V _{OL}	V _{CC} = 1.65V~5.5V, I _{OL} =100μA			0.1			0.1	V
		V _{CC} = 1.65V, I _{OL} =4mA			0.45			0.7	V
		V _{CC} = 2.3V, I _{OL} =8mA			0.3			0.45	V
		V _{CC} = 3.0V	I _{OL} =16mA		0.4			0.65	V
			I _{OL} =24mA		0.55			0.8	V
		V _{CC} = 4.5V, I _{OL} =32mA			0.55			0.8	V
Input Leakage Current	I _{I(LEAK)}	V _{CC} = 0~5.5V, V _{IN} =V _{CC} or GND			±5			±5	μA
Power OFF Leakage Current	I _{OFF}	V _{CC} = 0V, V _{IN} or V _{OUT} =5.5V			±10			±10	μA
Quiescent Supply Current	I _Q	V _{CC} = 1.65V~5.5V, V _{IN} =V _{CC} or GND I _{OUT} =0			10			10	μA
Additional Quiescent Supply Current	ΔI _Q	V _{CC} = 3V~5.5V, One input at V _{CC} -0.6V, other inputs at V _{CC} or GND			500			500	μA


■ DYNAMIC CHARACTERISTICS

PARAMETER	SYMBOL	TEST CONDITIONS		T _A =25°C			T _A =-40~+125°C			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
Propagation delay from input (A) to output (Y)	t _{PLH} / t _{PHL}	C _L =15pF	V _{CC} =1.8±0.15V	2.8		13	1		16	ns
			V _{CC} =2.5±0.2V	1.6		9.1	1		11.1	ns
			V _{CC} =3.3±0.3V	1.5		8.2	1		10.2	ns
			V _{CC} =5±0.5V	0.9		6.8	1		8.8	ns
		C _L =30 or 50pF	V _{CC} =1.8±0.15V	3.8		14.5	1		17.5	ns
			V _{CC} =2.5±0.2V	2		11.1	1		13.1	ns
			V _{CC} =3.3±0.3V	1.8		10.2	1		12.2	ns
			V _{CC} =5±0.5V	1.2		8.3	1		10.3	ns

■ OPERATING CHARACTERISTICS (f=10MHz, T_A =25°C, unless otherwise specified)


PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Input Capacitance	C _{IN}	V _{CC} = 3.3V, V _{IN} =V _{CC} or GND		4.5		pF
Power Dissipation Capacitance	C _{PD}	V _{CC} =1.8V		20		pF
		V _{CC} =2.5V		21		pF
		V _{CC} =3.3V		22		pF
		V _{CC} =5V		25		pF

■ TEST CIRCUIT AND WAVEFORMS



Note: C_L includes probe and jig capacitance.

V_{CC}	V_{IN}	t_R, t_F	V_M	C_L	R_L
$1.8V \pm 0.15V$	V_{CC}	$\leq 2ns$	$V_{CC}/2$	15pF	1M Ω
$2.5V \pm 0.2V$	V_{CC}	$\leq 2ns$	$V_{CC}/2$	15pF	1M Ω
$3.3V \pm 0.3V$	3V	$\leq 2.5ns$	1.5V	15pF	1M Ω
$5V \pm 0.5V$	V_{CC}	$\leq 2.5ns$	$V_{CC}/2$	15pF	1M Ω
$1.8V \pm 0.15V$	V_{CC}	$\leq 2ns$	$V_{CC}/2$	30pF	1K Ω
$2.5V \pm 0.2V$	V_{CC}	$\leq 2ns$	$V_{CC}/2$	30pF	500 Ω
$3.3V \pm 0.3V$	3V	$\leq 2.5ns$	1.5V	50pF	500 Ω
$5V \pm 0.5V$	V_{CC}	$\leq 2.5ns$	$V_{CC}/2$	50pF	500 Ω



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.