



UR6515D

CMOS IC

3A DDR BUS TERMINATION REGULATOR

■ DESCRIPTION

The **UR6515D** is a linear regulator sourcing or sinking continuous 2A or up to 3A transient peak current while regulating an output voltage to within 40mV in the DDR SDRAM bus terminator applications. It contains a high speed operational amplifier which provides fast load transient response.

The **UR6515D** output termination voltage tracks the reference voltage applied at V_{REF} pin. A resistor divider connected to V_{IN}, GND and V_{REF} pins is used to force the reference voltage to V_{REF} pin. Additional features include current limiting protection and thermal shutdown protection.

■ FEATURES



- * DDR1/ DDR2/DDR3 termination voltage applications
- * Sink and Source Current
 - 2A Continues Current
 - Peak 3A for DDR1&DDR2
 - Peak 2.5A for DDR3
- * Low output voltage offset within 20mV
- * Source and sink 3A peak current
- * Adjustable output voltage by external resistors
- * Integrated power MOS devices
- * Suspend to RAM(STR) functionality
- * Current Limiting Protection
- * Thermal Shutdown Protection

■ ORDERING INFORMATION

Ordering Number		Package	Packing
Lead Free	Halogen Free		
UR6515DL-SH2-R	UR6515DG-SH2-R	HSOP-8	Tape Reel


UR6515DG-SH2-R (1)Packing Type (2)Package Type (3)Green Package	(1) R: Tape Reel (2) SH2: HSOP-8 (3) G: Halogen Free and Lead Free, L: Lead Free
---	---

■ MARKING



HSOP-8


PIN CONFIGURATIONS



PIN DESCRIPTION

PIN NO	PIN NAME	PIN DESCRIPTION
1	V _{IN}	Power supply pin for the V _{OUT} output
2	GND	Ground pin
3	V _{REF}	Reference voltage input and active-low shutdown control pin
4	V _{OUT}	Output voltage pin
5, 7, 8	NC	No connect
6	V _{CNTL}	Power supply pin for the internal control circuits
Exposed Pad	GND	Ground pin

BLOCK DIAGRAM



■ ABSOLUTE MAXIMUM RATING (unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
V _{CNTL} Control Voltage	V _{CNTL}	6	V
V _{IN} Supply Voltage	V _{IN}	6	V
Power Dissipation (T _A =25°C)	P _D	1.33	W
Junction Temperature	T _J	+125	°C
Storage Temperature	T _{STG}	-65 ~ +150	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.
Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL DATA

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT
Junction to Ambient (Note 1)	θ _{JA}			75	°C/W
Junction to Case	θ _{JC}			28	°C/W

Note: θ_{JA} is measured in the natural convection at T_A = 25°C on a high effective thermal conductivity test board of JEDEC 51-7 thermal measurement standard.

■ RECOMMENDED OPERATING CONDITIONS (Note)

PARAMETER	SYMBOL	RATINGS	UNIT
V _{CNTL} Control Voltage	V _{CNTL}	5 or 3.3±5%	V
V _{IN} Supply Voltage	V _{IN}	2.5 ~ 1.5±3%	V
V _{REF} Input Voltage	V _{REF}	1.25 ~ 0.75±3%	V
Junction Temperature	T _J	-40 ~ +125	°C


Note: All voltage values are with respect to the network ground terminal unless otherwise noted.

■ ELECTRICAL CHARACTERISTICS (T_A=25°C, unless otherwise specified)

(V_{IN}=2.5V/1.8V/1.5V, V_{CNTL}=3.3V, V_{REF}=1.25V/0.9V/0.75V, C_{OUT} = 10μF (Electrolytic capacitor))

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
INPUT CURRENT						
Operation Current of V _{CNTL}	I _{CNTL}	I _{OUT} = 0A		1	2.5	mA
Standby Current	I _{STB}	V _{REF} < 0.2V, R _{LOAD} = 180Ω		50	90	μA
OUTPUT VOLTAGE (DDR/DDR II/DDR III)						
Output Voltage Offset (V _{REF} -V _{OUT})	V _{OS}	I _{OUT} = 0A	-20		20	mV
Load Regulation	ΔV _{LOAD}	I _{OUT} = ±2A	-20		20	mV
PROTECTION						
Current Limit	I _{LIMIT}	V _{IN} = 2.5V/1.8V/1.5V	3			A
Thermal Shutdown Temperature	T _{SD}	V _{CNTL} = 3.3V~5V	125	170		°C
Thermal Shutdown Hysteresis	ΔT _{SD}	V _{CNTL} = 3.3V~5V		35		°C
V_{REF} Shutdown						
Shutdown Threshold	V _{IH}	Enable	0.6			V
	V _{IL}	Shutdown			0.2	V

TYPICAL APPLICATIONS CIRCUITS









$R_1=R_2=100K\Omega$, $C_{OUT}=10\mu F$ (Electrolytic capacitor)+ $1000\mu F$ under the worst case testing condition







$C_{SS}=1\mu F$, $C_{IN}=470\mu F$ (Low ESR), $C_{CNTL}=47\mu F$

$$V_{REF} = \frac{R_2}{R_1 + R_2} V_{IN}(V), V_{OUT} \text{ track } V_{REF}$$




TYPICAL CHARACTERISTICS



■ TYPICAL CHARACTERISTICS (Cont.)



■ TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.