

**UT12P10H**

Preliminary



Power MOSFET

**-12A, -100V P-CHANNEL
POWER MOSFET****DESCRIPTION**

The UTC **UT12P10H** provide excellent $R_{DS(ON)}$, low gate charge and operation with low gate voltages. This device is suitable for use as a load switch or in PWM applications.

FEATURES


- * $R_{DS(ON)} \leq 180 \text{ m}\Omega$ @ $V_{GS} = -10\text{V}$, $I_D = -6.0\text{A}$
- * High Switching Speed
- * 100% Avalanche Tested

SYMBOL**ORDERING INFORMATION**

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
UT12P10HL-TN3-R	UT12P10HG-TN3-R	TO-252	G	D	S	Tape Reel

Note: Pin Assignment: G: Gate D: Drain S: Source

UT12P10HG-TN3-R	(1) Packing Type	(1) R: Tape Reel
	(2) Package Type	(2) TN3: TO-252
	(3) Green Package	(3) G: Halogen Free and Lead Free L: Lead Free

MARKING

■ ABSOLUTE MAXIMUM RATINGS ($T_A=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER			SYMBOL	RATINGS	UNIT
Drain-Source Voltage			V _{DSS}	-100	V
Gate-Source Voltage			V _{GSS}	±20	V
Drain Current	Continuous, V _{GSS} @-10V	T _C =25°C	I _D	-12	A
		T _C =100°C		-7.8	A
	Pulsed (Note 2)		I _{DM}	-24	A
Avalanche Energy	Repetitive (Note 3)		E _{AS}	152	mJ
Peak Diode Recovery dv/dt (Note 4)			dv/dt	15	V/ns
Power Dissipation (T _C =25°C)			P _D	41	W
Junction Temperature			T _J	+150	°C
Storage Temperature			T _{STG}	-55 ~ +150	°C

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Repetitive Rating: Pulse width limited by maximum junction temperature.

3. $L = 30\text{mH}$, $I_{AS} = -3.2\text{A}$, $V_{DD} = -50\text{V}$, $R_G = 25\Omega$, Starting $T_J = 25^{\circ}\text{C}$

4. $I_{SD} \leq -12\text{A}$, $di/dt \leq 200\text{A}/\mu\text{s}$, $V_{DD} \leq BV_{DSS}$, Starting $T_J = 25^{\circ}\text{C}$

■ THERMAL DATA

PARAMETER	SYMBOL	RATINGS	UNIT
Junction to Ambient	θ_{JA}	110	$^{\circ}\text{C}/\text{W}$
Junction to Case	θ_{JC}	3.05 (Note)	$^{\circ}\text{C}/\text{W}$

Note: Device mounted on FR-4 substrate P_c board, 2oz copper, with 1inch square copper plate.


■ ELECTRICAL CHARACTERISTICS ($T_J=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS							
Drain-Source Breakdown Voltage		BV _{DSS}	I _D =-250μA, V _{GS} =0V	-100			V
Drain-Source Leakage Current		I _{DSS}	V _{DS} =-100V, V _{GS} =0V			-1	μA
Gate- Source Leakage Current	Forward	I _{GSS}	V _{GS} =+20V			+100	nA
	Reverse		V _{GS} =-20V			-100	nA
ON CHARACTERISTICS							
Gate Threshold Voltage		V _{GS(TH)}	V _{DS} =V _{GS} , I _D =-250μA	-2.0		-4.0	V
Static Drain-Source On-State Resistance		R _{DS(ON)}	V _{GS} =-10V, I _D =-6.0A			180	mΩ
DYNAMIC PARAMETERS							
Input Capacitance		C _{ISS}	V _{DS} =-25V, V _{GS} =0V, f=1MHz		1149		pF
Output Capacitance		C _{OSS}			69		pF
Reverse Transfer Capacitance		C _{RSS}			13		pF
SWITCHING PARAMETERS							
Total Gate Charge		Q _G	V _{DS} =-80V, V _{GS} =-10V, I _D =-12A		22		nC
Gate to Source Charge		Q _{GS}			9.3		nC
Gate to Drain ("Miller") Charge		Q _{GD}			5.1		nC
Turn-ON Delay Time		t _{D(ON)}	V _{DD} =-50V, I _D =-12A, R _G =3Ω		9.7		ns
Rise Time		t _R			10		ns
Turn-OFF Delay Time		t _{D(OFF)}			20		ns
Fall-Time		t _F			20		ns
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS							
Maximum Body-Diode Continuous Current		I _S				-12	A
Maximum Body-Diode Pulsed Current		I _{SM}	(Note 1)			-24	A
Drain-Source Diode Forward Voltage		V _{SD}	I _S =-12A, V _{GS} =0V (Note 2)			-1.4	V
Body Diode Reverse Recovery Time (Note 1)		t _{rr}	I _S =-12A, V _{GS} =0V,		123		ns
Body Diode Reverse Recovery Charge		Q _{rr}	dI _F /dt=100A/μs		160		nC


Notes: 1. Pulse Test: Pulse width $\leq 300\mu\text{s}$, Duty cycle $\leq 2\%$.

2. Essentially independent of operating ambient temperature.

■ TEST CIRCUITS AND WAVEFORMS




Peak Diode Recovery dv/dt Test Circuit




Peak Diode Recovery dv/dt Waveforms


■ TEST CIRCUITS AND WAVEFORMS




Switching Test Circuit




Switching Waveforms




Gate Charge Test Circuit



Gate Charge Waveform



Unclamped Inductive Switching Test Circuit



Unclamped Inductive Switching Waveforms

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.