


**UT17NN10***Power MOSFET***17A, 100V DUAL N-CHANNEL
ENHANCEMENT MODE POWER
MOSFET****DESCRIPTION**


The UTC **UT17NN10** is a dual N-Channel enhancement mode power MOSFET, it provides designer with fast switching speed, ruggedized device design, low on-resistance and cost-effectiveness.

FEATURES

- * $R_{DS(ON)} \leq 105 \text{ m}\Omega$ @ $V_{GS}=10\text{V}$, $I_D=8.5\text{A}$
- * Fast Switching Speed
- * Simple Drive Requirement



SOP-8


SYMBOL**ORDERING INFORMATION**

Ordering Number		Package	Pin Assignment								Packing
Lead Free	Halogen Free		1	2	3	4	5	6	7	8	
UT17NN10L-S08-R	UT17NN10G-S08-R	SOP-8	S1	G1	S2	G2	D2	D2	D1	D1	Tape Reel

Note: Pin Assignment: G: Gate D: Drain S: Source

UT17NN10G-S08-R		(1) Packing Type	(1) R: Tape Reel
		(2) Package Type	(2) S08: SOP-8
		(3) Green Package	(3) G: Halogen Free and Lead Free, L: Lead Free

■ MARKING



■ ABSOLUTE MAXIMUM RATINGS ($T_A=25^{\circ}\text{C}$ unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Drain-Source Voltage		V_{DS}	100	V
Gate-Source Voltage		V_{GS}	± 20	V
Drain Current	Continuous(Note 3)	I_D	17	A
	Pulsed(Note 2)	I_{DM}	34	A
Peak Diode Recovery dv/dt (Note 4)		dv/dt	2.7	V/ns
Power Dissipation		P_D	2	W
Junction Temperature		T_J	+150	$^{\circ}\text{C}$
Storage Temperature		T_{STG}	-55 ~ +150	$^{\circ}\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Repetitive Rating: Pulse width limited by maximum junction temperature.

3. $I_{SD} \leq 8.0\text{A}$, $di/dt \leq 200\text{A}/\mu\text{s}$, $V_{DD} \leq BV_{DS}$, Starting $T_J = 25^{\circ}\text{C}$

■ THERMAL DATA

PARAMETER	SYMBOL	RATINGS	UNIT
Junction to Ambient	θ_{JA}	62.5	$^{\circ}\text{C}/\text{W}$

Note: Device mounted on FR-4 substrate P_C board, 2oz copper, with 1inch square copper plate.


■ ELECTRICAL CHARACTERISTICS ($T_J=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS							
Drain-Source Breakdown Voltage		BV _{DSS}	V _{GS} =0V, I _D =250μA	100			V
Drain-Source Leakage Current		I _{DSS}	V _{DS} =100V, V _{GS} =0V			1	μA
Gate-Source Leakage Current	Forward	I _{GSS}	V _{DS} =0V, V _{GS} =20V			100	nA
	Reverse		V _{DS} =0V, V _{GS} =-20V			-100	nA
ON CHARACTERISTICS							
Gate Threshold Voltage		V _{GS(TH)}	V _{DS} =V _{GS} , I _D =250μA	1.0		2.5	V
Drain-Source On-State Resistance (Note 1)		R _{DS(ON)}	V _{GS} =10V, I _D =8.5A			105	mΩ
DYNAMIC PARAMETERS							
Input Capacitance		C _{ISS}	V _{DS} =25V, V _{GS} =0V, f=1.0MHz		370		pF
Output Capacitance		C _{OSS}			44		pF
Reverse Transfer Capacitance		C _{RSS}			33		pF
SWITCHING PARAMETERS							
Total Gate Charge (Note 1)		Q _G	V _{DS} =80V, V _{GS} =10V, I _D =8.0A I _G =1mA (Note 1, 2)		17		nC
Gate-Source Charge		Q _{GS}			3		nC
Gate-Drain Charge		Q _{GD}			4.2		nC
Turn-ON Delay Time (Note 1)		t _{D(ON)}	V _{DS} =50V, V _{GS} =10V, I _D =8.0A, R _G =3.0Ω (Note 1, 2)		10		ns
Turn-ON Rise Time		t _R			16		ns
Turn-OFF Delay Time		t _{D(OFF)}			23		ns
Turn-OFF Fall Time		t _F			19		ns
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS							
Maximum Continuous Drain-Source Diode Forward Current		I _S				17	A
Maximum Pulsed Drain-Source Diode Forward Current		I _{SM}				34	A
Drain-Source Diode Forward Voltage (Note 1)		V _{SD}	I _S =17A, V _{GS} =0V			1.2	V
Body Diode Reverse Recovery Time (Note 1)		t _{rr}	I _S =17A, V _{GS} =0V,		55		ns
Body Diode Reverse Recovery Charge		Q _{rr}	dI _F /dt=100A/μs		63		nC


Notes: 1. Pulse Test : Pulse width $\leq 300\mu\text{s}$, Duty cycle $\leq 2\%$.

2. Essentially independent of operating temperature.

■ TEST CIRCUITS AND WAVEFORMS




Peak Diode Recovery dv/dt Test Circuit




Peak Diode Recovery dv/dt Waveforms


■ TEST CIRCUITS AND WAVEFORMS




Switching Test Circuit




Switching Waveforms




Gate Charge Test Circuit



Gate Charge Waveform



Unclamped Inductive Switching Test Circuit



Unclamped Inductive Switching Waveforms

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.